

RIJEKA low cut safety shoes

» Shoes » Safety shoes » Low cut

Technical sheet

RIJEKA low cut safety shoes

Product code: 3185-S3



upper	corrected cow leather with pattern in a thickness of 1,6 – 1,8 mm
lining	MESH fabric with absorbency
inner insole	lightweight polyurethan foam, coated with textile MESH, antistatic
outsole	PU – resistant to fuel oils, antistatic, antislip
size	35 – 50
standard	EN ISO 20345:2022
version	S3 FO SR – with steel toe cap and midsole

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	Yes
WPA Water resistant upper	Yes
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No

RIJEKA low cut safety shoes

» Shoes » Safety shoes » Low cut

CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes
P Midsole penetration protection	Yes
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20345:2023
Shoe marking	S3

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - widht	Sales box - length	Sales box - height	Group packaging - widht	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
35	0,91 kg	1,16 kg	200 mm	315 mm	110 mm	420 mm	580 mm	335 mm	12,40 kg	0,0 mm
36	0,89 kg	1,14 kg	200 mm	315 mm	110 mm	420 mm	580 mm	335 mm	12,20 kg	0,0 mm
37	0,92 kg	1,17 kg	200 mm	315 mm	110 mm	420 mm	580 mm	335 mm	12,40 kg	0,0 mm
38	0,94 kg	1,19 kg	200 mm	315 mm	110 mm	420 mm	580 mm	335 mm	12,80 kg	0,0 mm
39	1,02 kg	1,28 kg	200 mm	315 mm	110 mm	420 mm	580 mm	335 mm	13,60 kg	0,0 mm
40	1,04 kg	1,29 kg	200 mm	315 mm	110 mm	420 mm	580 mm	335 mm	13,60 kg	0,0 mm
41	1,11 kg	1,36 kg	200 mm	315 mm	110 mm	420 mm	580 mm	335 mm	14,20 kg	0,0 mm
42	1,12 kg	1,39 kg	200 mm	315 mm	110 mm	420 mm	580 mm	335 mm	14,60 kg	0,0 mm
43	1,10 kg	1,41 kg	205 mm	325 mm	115 mm	410 mm	600 mm	350 mm	15,00 kg	0,0 mm
44	1,14 kg	1,40 kg	205 mm	325 mm	115 mm	410 mm	600 mm	350 mm	15,00 kg	0,0 mm
45	1,27 kg	1,54 kg	210 mm	350 mm	120 mm	435 mm	630 mm	370 mm	15,80 kg	0,0 mm
46	1,26 kg	1,53 kg	210 mm	350 mm	120 mm	435 mm	630 mm	370 mm	16,20 kg	0,0 mm
47	1,30 kg	1,57 kg	210 mm	350 mm	120 mm	435 mm	630 mm	370 mm	16,60 kg	0,0 mm
48	1,30 kg	1,57 kg	210 mm	350 mm	120 mm	435 mm	630 mm	370 mm	17,00 kg	0,0 mm
49	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm
50	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm

Business parameters

Tarric	64034000
Country	CN

RIJEKA low cut safety shoes

» Shoes » Safety shoes » Low cut

Weight	1,50 kg
Add Unit	NPR
Add Quantity	1