



EXTREMELY SPECIALIZED



PANTHER/ANATOMIC
WATERPROOF
LEONARDO CI
32274 03LA
S3 WR CI SRC HRO UNI EN ISO 20345:2012

UPPER	Water repellent full grain leather
LINING	waterproof membrane IN-DRY that unlike traditional sock lining, is applied directly on the upper and integrally seals all seams creating a barrier to water and keeping the foot warm and dry. Breathable and high thermal power. PRIMALOFT ® Gold Insulation Eco Thermo-regulating, insulating and waterproof padding, it keeps the foot warm even in exceptionally cold environments. Composed for 90% by recycled fibers, it has a longer life, dries quickly and promotes the maintenance of temperature throughout the body
INSOLE	HEAT COMFY - Thermoformed. Needle-tufted felt and aluminium fabric that is anti-bacterial, breathable and absorbent. It isolates against cold and heat, used in CI and HI footwear.
SOLE	PU/RUBBER BASF PUR Elastopan ® polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces. Polyurethane outsole, with an elevated grip, resistant to up to a 300°C (HRO certified) , guarantees the maximum levels of slip resistance. Resistant to corrosion by oils and hydrocarbons. It leaves no mark on the surface.
LAST	The anatomical shape of the injected sole, unlike removable insoles, is inalterable for the entire lifetime of the shoe. The ANATOMIC SOLE , following the natural morphology of the foot, provides a natural support to all its points, ensuring maximum comfort
TOE CAP	The POWER CAP is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules. Being metal-free is undetectable by a meta detector, and helps to maintain a constant body temperature. It provides maximum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps. It is compliant with CSA Canada regulations and exceeds the EN-ISO12568 requirements.
MIDSOLE	TEXON ENIGMA ZERO HT2 Non-metallic antistatic, flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibres. It ensures perfect thermal insulation Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTM F2413-18
ANTI-TORSION SUPPORT	COMPOSHANK Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.
ANTI-STATIC DEVICE	SILVER STRIP DISCHARGE (SSD) Conductive cotton tape and silver threads inside the upper and in contact with the foot. It is an anti-static device that guarantees greater safety than the standard, increases the dispersive capacity of the electrostatic charges throughout the life of the shoes.
WEIGHT SIZE 42	950 gr
SIZES 38-48	

HEAT COMFY



FEATURES

 SHOCK ABSORPTION IN THE HEEL	 OIL AND HYDROCARBONS RESISTANT SOLE	 TOE CAP
 NO MARKING SOLE	 ANTISTATIC FOOTWEAR	 BREATHABLE UPPER
 WATER-REPELLENT UPPER	 ANTIPERFORATION MIDSOLE	 HRO- HEAT RESISTANT SOLE (300°C)
 CI- COLD INSULATION	 WR- WATERPROOF	

PLUS

	
---	---

TECHNOLOGIES

	
	