

GET COMFORTABLE



ABOUTBLU/ANATOMIC

CONCRETE

OIKOS

MID

33275 10LA

SRC **DGUV 112-191** UNI EN ISO 20345:2012

ECO-SOFT

FEATURES

OIL AND HYDROCARBONS RESISTANT SOLE

ANTISTATIC FOOTWEAR

ANTIPERFORATION MIDSOLF

ECHNOLOGIES

TOE CAP

BREATHABLE UPPER

	Water repellent and breathable nubuk leather with scuff cap.	UPPER
	PLASMAFEEL Lining in 3D fabric that keeps the foot constantly cool and dry thanks to the instantaneous absorption of sweat and its immediate dispersion outside of the shoe. Breathable, antibacterial, resistant to wear and abrasion.	LINING
SHOCK ABSORPTION IN THE HEEL	ECO-SOFT Thermoformed . Runproof , multi -layered , antistatic fabric , that is antibacterial , breathable and absorbent with anti-fungus activated carbons . Shock absorbing heel and plantar arch support. ECO FRIENDLY- RECYCLED MATERIAL	INSOLE
NO MARKING SOLE	PU/PU DUAL DENSITY BASF PUR Elastopan® polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces. Polyurethane outsole, with an elevated grip, resistant to wear, oils and hydrocarbons. System of energy absorption on the heel. It leaves no mark on the surface.	SOLE
	The anatomical shape of the injected sole, unlike removable insoles, is inalterable for the entire lifetime of the shoe. The Anatomic sole, following the natural morphology of the foot, provides a natural support to all its points, ensuring maximum comfort	LAST
WATER-REPELLENT UPPER	The POWER CAP is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules.Being metal-free is is undetactable by a meta detector, and helps to maintain a constant body temperature. It provides maxmum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps. It exceeds the EN-ISO 12568 requirements.	TOE CAP
QUISMAFEE	TEXON ENIGMA ZERO HT2 Non-metallic antistatic, flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibres. It ensures perfect thermal insulation Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTM F2413-18	MIDSOLE
AWTHERSKE	COMPOSHANK Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on	ANTI-TORSION SUPPORT

SILVER STRIP DISCHARGE (SSD) Conductive cotton tape and silver threads inside

the upper and in contact with the foot. It is an anti-static device that guarantees greater

safety than the standard, increases the dispersive capacity of the electrostatic charges

ladders, where foot support is not complete.

throughout the life of the shoes.

WEIGHT SIZE 42 750 gr

SUPPORT

DEVICE

ANTI-STATIC

SIZES 38-48